





ABOUT THE PRODUCT

Wynn's Heavy Duty Tech 1 Coolant is a 50/50 Pre-Mix formulated with long life anti-freeze, anti-boil propylene glycol technology.

Colour	Туре	Product Number	Pack Size	Carton Qty.
Red	50/50 Pre-Mix	57510	205L	1

Wynn's Manufactured & Distributed by ITW AAMTech An Illinois Tool Works Company, 1-9 Nina Link, Dandenong VIC 3175 Tel: 1800 177 989 | Email: wynnsaus@wynns.net | Website: www.wynnspro.com.au ABN 63 004 235 063

The data concerning properties and applications of the indicated products are offered in good faith and are based on our research and practical experiences. Due to the versatility of the application possibilities, it is impossible to mention all details and we do not assume any obligations or responsibilities resulting from this. When a new edition appears due to the technical development, the preceding data are no longer valid.





ADVANTAGES

Wynn's Heavy Duty Tech 1 Coolant, containing propylene glycol, is an advanced blend of Organic Long Life Inhibitors that provide maximum corrosion, anti-boil, and anti-freeze protection.

BENEFITS

Wynn's Heavy Duty Tech 1 Coolant provides the following benefits:

- 01 Does not contain phosphates, borates, silicates, amines, nitrates or tannins
- 02 5 years or 250,000 km service life (whichever comes first) when used as recommended
- 03 Anti-boil protection
- 04 Corrosion protection
- 05 Anti-freeze protection (to -34°C)

DIRECTIONS OF USE

- 1. Drain cooling system and flush with clean water
- 2. Use Wynn's Radiator Flush & De-Oiler (Product No. 65010) if the cooling system is dirty
- 3. Add Wynn's Heavy Duty Tech 1 Coolant to the radiator
- 4. Run engine, follow air-bleeding procedures as per vehicle manufacturer's instructions and check level when cool.
- 5. Do not mix with any other coolant or dilute with water as this will adversely affect the product's performance
- 6. Maximum useful life of 5 years or 250,000km

note: if spilt on paintwork wash off with water immediately.

APPLICATIONS

Wynn's Heavy Duty Tech 1 Coolant suitable for use in the cooling systems of petrol and diesel engines of cars, trucks, buses, off-road equipment, stationary engines and boats. Standards: AS2108 - 2004 (Type A), ASTM D1384, ASTM D4340,

The data concerning properties and applications of the indicated products are offered in good faith and are based on our research and practical experiences. Due to the versatility of the application possibilities, it is impossible to mention all details and we do not assume any obligations or responsibilities resulting from this. When a new edition appears due to the technical development, the preceding data are no longer valid.