



ABOUT THE PRODUCT

Wynn's Viscotene is a strongly adhesive and highly viscous semi-synthetic lubricant that is exceptionally water repellent. Combined with the unique Wynn's Friction Proofing® Package, Wynn's Viscotene has outstanding viscosity characteristics over a wide range of temperatures.

Product Number	Pack Size	Carton Qty.
80005	5L	3



Wynn's Manufactured & Distributed by ITW AAMTech
An Illinois Tool Works Company, 1-9 Nina Link, Dandenong VIC 3175
Tel: 1800 177 989 | Email: wynnsaus@wynns.net | Website: www.wynnspro.com.au
ABN 63 004 235 063

The data concerning properties and applications of the indicated products are offered in good faith and are based on our research and practical experiences. Due to the versatility of the application possibilities, it is impossible to mention all details and we do not assume any obligations or responsibilities resulting from this. When a new edition appears due to the technical development, the preceding data are no longer valid.

**WYNN'S VISCOTENE****ADVANTAGES**

Wynn's Viscotene is a semi-synthetic lubricant formulated to:

- Quieten noisy open gears and reduce equipment temperature
- Prevent wear, oxidation and corrosion of metallic components
- Reduce vibration, noise and oil lubricant leaks
- Continuous operating temperature range 5°C to 130°C

BENEFITS

Wynn's Viscotene has been designed to provide the following benefits:

- 01 Provide tenacious resistance to water wash-off, chemical attack and steam exposure
- 02 Provide extreme-pressure and anti-wear for high load carrying capability
- 03 Reduce lubricant consumption
- 04 Extend maintenance intervals

DIRECTIONS OF USE

Wynn's Viscotene should be applied directly onto the application area.

APPLICATIONS

- Where tenacious adhesion and unusual viscosity is needed
- Conveyor systems, open gears, chains, belts and elevators
- Where lubricant splatter must be avoided
- Wire ropes and blocks
- Hydraulic press guide columns
- Open sprockets and chains, as seen on concrete mixers
- Constant velocity joints
- Where hot or cold water, steam or chemicals are a problem

