



ABOUT THE PRODUCT

Wynn's Viscotene FG is a semi-synthetic lubricant displaying tenacious resistance to water wash-off, chemical attack and steam exposure. It contains extremely tacky polymers of very high viscosity index, high film-strength surface-active compounds, oxidation and corrosion inhibitors. This, combined with the Wynn's Friction Proofing package of extreme pressure compounds, significantly reduces the possibility of extreme wear, seizing and at worst, failure of the lubricated components.

Product Number	Pack Size	Carton Qty.
79880	375g	12





ADVANTAGES

Once applied, Wynn's Viscotene FG, containing Wynn's Friction Proofing, will remain in place on equipment that tends to drop or throw-off conventional lubricants (such as conveyors, chains and wire ropes). It will maintain adhesion even under severe conditions such as water wash, steam, and when exposed to chemically harsh environments.

BENEFITS

Wynn's Viscotene FG has been formulated to provide the following benefits:

- 01 Overall wear reduction.
- 02 Reduced corrosion and water wash out.
- 03 Increased lubrication intervals.
- 04 Reduces spattering and noise.
- 05 Performs well under a broad range of operating temperatures.

DIRECTIONS OF USE

Shake the aerosol until the ball rattles, hold upright and spray directly onto the parts to be lubricated and protected. For maximum adhesion and best results, avoid overspraying and remove any excess residue of Wynn's Viscotene FG.

Place a protective covering over plastics, rubber and painted surfaces to protect them from overspray. Whilst the product is non-flammable, the propellant is flammable. Allow propellant to evaporate before the non-flammable characteristics of Wynn's Viscotene FG can come into effect.

APPLICATIONS

Wynn's Viscotene FG is a multi-functional lubricant and may be used in:

- Conveyor systems, open gears, chains, belts and elevators.
- Wire ropes and blocks.
- Hydraulic press guide columns.
- Open sprockets and chains on concrete mixers.
- Constant velocity joints.
- Chain drive of bicycles, motorcycles and chainsaws.
- Machine tool lead screws, ways and tables.
- Any general lubrication exposed to water, steam or chemicals

Wynn's Viscotene FG is suitable for use in the construction, transport, marine, rural and all manufacturing industries