



WYNN'S ULTRA SUPREME GREASE



PROFESSIONAL RANGE



ABOUT THE PRODUCT

Wynn's Ultra Supreme Grease is a premium lithium soap thickened grease of NLGI Grade No.2 consistency formulated to outperform ordinary No.2 greases in all applications. Combined with the unique Wynn's Friction Proofing® Package, Wynn's Ultra Supreme Grease is particularly suited to industry and fleet applications including light/heavy transport, agriculture, mining and marine in the heavily loaded, extreme pressure, high wear conditions.

Product Number	Pack Size	Carton Qty.
50545	450g cartridge	20
50525	2.5kg tub	6
50520	20kg pail	1
50555	55kg drum	1
50575	175kg drum	1



Wynn's Manufactured & Distributed by ITW AAMTech
An Illinois Tool Works Company, 1-9 Nina Link, Dandenong VIC 3175
Tel: 1800 177 989 | Email: wynnsaus@wynns.net | Website: www.wynnspro.com.au
ABN 63 004 235 063

The data concerning properties and applications of the indicated products are offered in good faith and are based on our research and practical experiences. Due to the versatility of the application possibilities, it is impossible to mention all details and we do not assume any obligations or responsibilities resulting from this. When a new edition appears due to the technical development, the preceding data are no longer valid.



WYNN'S ULTRA SUPREME GREASE

ADVANTAGES

Wynn's Ultra Supreme Grease prevents corrosion of metallic components under humid & wet conditions.

Wynn's Ultra Supreme Grease provides high extreme pressure properties, with a drop point 195°C and an operating temperature -20°C to 160°C.

BENEFITS

Wynn's Ultra Supreme Grease is formulated to provide the following benefits:

- 01 Displays extremely good water wash-out resistance
- 02 Resists breakdown as a result of mechanical action
- 03 Prevents corrosion of metallic components under humid & wet conditions
- 04 Prevents operating temperatures escalating under high load conditions
- 05 Prevents scuffing and galling through extreme-pressure and anti-wear properties
- 06 Allows longer intervals between greasing

DIRECTIONS OF USE

Wynn's Ultra Supreme Grease may be applied either manually or by automatic greasing systems designed to pump an NLGI No.2 grease. It is always good practice not to mix varied brands and types of greases. If the type of grease is unknown, the area to be lubricated should be cleaned or purged prior to application.

APPLICATIONS

Wynn's Ultra Supreme Grease is suitable for industrial and automotive bearings, grease lubricated journal bearings, flexible gear couplings, shackles and torsion bars, oscillating bucket pins, lubrication of chassis components, clutch bearings and drive line bearings, cams, ways and sliding elements.

It is also suitable for kingpins and bushes, walking beams, universal joints, ring feeders, turn tables, and slack adjusters.

If this lubricant is used within New Zealand under an MPI **Approved Maintenance Compound (non-Dairy)** as an **C13 product**, it must be confined in enclosed housings.

